

Specifications Mode: C90S

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
	CPU	HI3518E V200
Image Capture	Image sensor	GC2053
	Minimum Illumination	0.3-0.5Lux(color mode), 0 Lux(B&W mode)
	Lens	HLC-GC2053-V40-V2.0 module
	View Angle	140°(Diagonal)
	Nightvision	Photosensitive filter with auto-switching, 8pcs 940nm SMD IR LED, IR irradiation distance:5-10 m
Video	Encode format	H.264 main profile@levels:4.0/Motion-JPEG
	Three Stream	Main Stream:1080p(1920X1080)@15fps Sub Stream:360p(640X360)@15fps Third Stream:180p(320X180)@15fps
	Bit Rate	128~4096kbps
	Maximum frame rate	15fps
	Image adjustment	Auto
Audio	Input	Built-in 38db microphone
	Output	N/A
	Sampling frequency /Bit width	8KHz/16bit
	Compression standard /code rate	ADPCM/32kbps
Network	Ethernet	N/A (connect via AP hotspot mode)
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
Memory	Socket	TF Push-push socket,Maximum support 128GB; Cloud Storage
Alarm	Alarm Trigger	Motion detection
Physical Environmental	Rated voltage	DC5V±5%
	Power supply	Built-in 1500mAh batteries
	Power consumption	Rated power: 2.05W (with infrared lights on) Maximum power: 3.30W
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Gross: 52 g(Note: in kind prevail)
	Package size	128x99x48mm (L×W×H)