

Specifications Model: C18S

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/2.7 inch 1080p Progressive Scan CMOS
	Minimum Illumination	0.3~0.5Lux (Color mode) ,0.1Lux (B&W Mode)
	Lens	4.0mm@F2.5
	View Angle	84°
	Nightvision	Dual Filter,IR-Cut, 2pcs 850nm IR LED; 2 LED while lights,full colored night vision IR irradiation distance:15m
Video	Encode format	H.264 main profile@levels:4.0/Motion-JPEG
	Three Stream	Main Stream:1080p(1920X1080)@15fps Sub Stream:360p(640X360)@15fps Third Stream:180p(320X180)@10fps
	Bit Rate	128~4096kbps
	Maximum frame rate	15fps
	Image adjustment	Contrast、Brightness、Saturation、Hue
Audio	Input	Waterproof microphone -38db
	Output	Built-in 95 DB siren.
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
	Wireless LAN	IEEE802.11b/g/n
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
Memory	Socket	TF Push-push socket,Maximum support 128GB; Cloud Storage
Alarm	Alarm Trigger	Motion detection
Physical Environmental	Rated voltage	DC12V/2A
	Power consumption	Related power:3.48W(IR on) Max power:7.08W(Pan/Tilt on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Gross: TBD g(Note: in kind prevail)
	Package size	N/A